

HIGH TEMPERATURE SILICONE MULTICORE CABLES

Cable Construction

Tinned copper conductors, all Class 5 stranding
Silicone insulation
Silicone sheath of tear resistance compound

Operating Temperature

Working temperature -60°C to +180°C Static
Minimum permissible ambient temperature -60°C
Minimum ambient temperature for flexible operation -40°C
Short term to 220°C

Temperature Range

Rated Voltage

450/750V

Bending Radius

Relevant Standards

Properties

Resistance to High Molecular Oils, Animal and Vegetable Fats, Alcohols, Diluted Acids,
Low Smoke, Halogen Free.

CMI Head Office NSW | (02) 9807 6155 | F3, 3-29 Birnie Ave, Lidcombe, NSW, 2141 | nswsales@cmielectrical.com.au
CMI QLD-Brisbane
(07) 3863 0749
485A Zillmere Road,
Zillmere QLD 4034
southqldsales@cmielectrical.com.au

CMI QLD – Rockhampton
(07) 4921 0978
Shop 3 at 76 Hollingsworth Street,
North Rockhampton Qld 4701
northqldsales@cmielectrical.com.au

CMI VIC
(03) 9532 1233
3 Dissik Street,
Cheltenham VIC 3192
vicsales@cmielectrical.com.au

CMI WA
(08) 9358 1788
36 Division Street,
Welshpool WA 6106
wasales@cmielectrical.com.au