

BRAIDED PAIRS MULTI CHANNEL AUDIO CABLES - HIGHLY FLEXIBLE

AUDIO CABLES

Use
 Microphone cable with individually Copper Braided screen, each pair with outer jacket of Hi-Flex PVC and completed with a soft Flexible outer jacket of Black Hi-Flex PVC.
 Ultra flexibility achieved by 30/0.08 strands of bare copper with Copper outer braid screen of 95%.

Insulation
 Hi-Flex PVC
Sheath
 Hi-Flex PVC
Screen
 Tinned Copper Screen
Conductor
 Bare Copper
Pack
 100 or 500 meter reels
Core Colour
 As per Chart C of Section 10.

HCYNB SERIES



Part Number	Nearest AWG	No. Of Pairs	Cond. No. / Dia.	Insulation Type - Thickness mm	Sheath Dia.	Screen
HCYNB04	26	4	30/0.08 BC	0.40	12.20	TC Braid
HCYNB06	26	6	30/0.08 BC	0.40	14.50	TC Braid
HCYNB08	26	8	30/0.08 BC	0.40	15.70	TC Braid
HCYNB12	26	12	30/0.08 BC	0.40	19.00	TC Braid
HCYNB16	26	16	30/0.08 BC	0.40	21.40	TC Braid

CMI Head Office NSW | (02) 9807 6155 | F3, 3-29 Birnie Ave, Lidcombe, NSW, 2141 | nswsales@cmielectrical.com.au
CMI QLD-Brisbane
 (07) 3863 0749
 485A Zillmere Road,
 Zillmere QLD 4034
southqldsales@cmielectrical.com.au

CMI QLD – Rockhampton
 (07) 4921 0978
 Shop 3 at 76 Hollingsworth Street,
 North Rockhampton Qld 4701
northqldsales@cmielectrical.com.au

CMI VIC
 (03) 9532 1233
 3 Dissik Street,
 Cheltenham VIC 3192
vicsales@cmielectrical.com.au

CMI WA
 (08) 9358 1788
 36 Division Street,
 Welshpool WA 6106
wasales@cmielectrical.com.au