

AXLINK CABLE

AUDIO CABLES

Use
 Screened Control cable which acts as a master to slave with power.

Cable Construction
 1 pair 7/0.25mm Bare Copper with PVC insulation and overall aluminium polyester screen and two cores 16/0.25mm Bare Copper with PVC insulation, laid up together and overall PVC sheath.

Sheath Colour
 Light Green.

Note
 These cables are not suitable for direct connection to mains supply. Minimum order quantity will apply.

Pack
 100 or 500 meter reels.

AXLINK CABLE



Part Number	No. Of Cores	Cond. No. / Dia.	Core Colour	Insulation	Screen	Sheath Type Dia.
HCY662	1 Pair	7/0.25 BC	White + Blue	PVC	AL / PE	PVC 6.50
	2 Cores	16/0.25 BC	Red + Black	PVC	-	

CMI Head Office NSW | (02) 9807 6155 | F3, 3-29 Birnie Ave, Lidcombe, NSW, 2141 | nswsales@cmielectrical.com.au
CMI QLD-Brisbane
 (07) 3863 0749
 485A Zillmere Road,
 Zillmere QLD 4034
southqldsales@cmielectrical.com.au

CMI QLD – Rockhampton
 (07) 4921 0978
 Shop 3 at 76 Hollingsworth Street,
 North Rockhampton Qld 4701
northqldsales@cmielectrical.com.au

CMI VIC
 (03) 9532 1233
 3 Dissik Street,
 Cheltenham VIC 3192
vicsales@cmielectrical.com.au

CMI WA
 (08) 9358 1788
 36 Division Street,
 Welshpool WA 6106
wasaless@cmielectrical.com.au